



ABS SURFACE MOUNTING CEILING IW-100 T LOUDSPEAKER

- 2-way with 4" woofer and 1" dome tweeter
- Rated power 1/2/4/7.5/15W RMS with 100V transformer
- Frequency response 60-20,000Hz, sensitivity 1W/1m of 88dB
- Dispersion (-6dB) 1kHz/4kHz 80°/150°



Bruto excl. 45,95

ABS SURFACE MOUNTING CEILING IW-200 TCP LOUDSPEAKER

- 2-way with 8" woofer and 1" dome tweeter
- Rated power 1/2/4/7.5/15/30W RMS
- 100V transformer
- Frequency response 40-20,000Hz, sensitivity 1W/1m of 90dB
- ABS base
- Dispersion (-6dB) 1kHz/4kHz 80°/140°



Bruto excl. 95,95

PVC FLUSH MOUNTING WALL FPS-5T LOUDSPEAKER

- 2-way
- Rated power 20W at 4 Ohm
- Dispersion (-6dB) 1kHz/4kHz 150°/70°
- Power 6 Watt with 100V transformer
- Woofer 5" ¼ with dome tweeter
- SPL 1W/1m 87dB
- Dispersion (-6dB) 1kHz/4kHz 140°/100°
- White colour



Bruto excl. 69,95

MULTIFUNCTION SOUND SPEAKER WS 506 T-VA

- Conforming to world standards for voice alarms (BS5839 part 8 included) requiring that in the event of fire the whole loudspeaker circuit shall not be affected by one or more loudspeakers damaged by localized fire
- It features ceramic connectors that can resist to temperatures higher than 650°C
- Fire-resistant internal cable
- Pair of input/output cable sleeves for easy wiring
- 150° thermal fuse for insulating the loudspeaker from the circuit in case of fire detection



Bruto excl. 49,95